



MACCO ORGANIQUES INC.

100 McArthur, suite 112, Salaberry-de-Valleyfield, Quebec, Canada, J6S 4M5

Tel: (450) 371-1066, Fax: (450) 371-5519

Web page address: www.macco.ca, Email: macco@macco.ca



THE MANUFACTURING PROCESS OF THE PRODUCT BELOW IS COVERED BY A REGISTERED FSSC 22000 FOOD SAFETY SYSTEM

Date: March 21, 2019

Supersedes: December 01, 2017

Ref #: S40153-A-G

DC #: 19-051

SPECIFICATIONS SODIUM BENZOATE FCC-NF DENSE

GENERAL

Molecular formula: $C_7H_5NaO_2$
Molecular weight: 144.11 g/mol

CAS #: 532-32-1
EEC #: E-211

Description

White, odorless or nearly odorless, granular solid.

Parameters

Identification
Assay (anhydrous basis)
Water
Alkalinity (as NaOH)
Heavy metals (as Pb)
Lead

Specifications

Passes test
99.0 to 101.0%
1.5% Max.
Passes test (0.04% Max.)
10 µg/g Max.
2 mg/kg Max.

OVI and RS: This material conforms to the USP<467>, ICH Q3C and EP 5.4 requirements for organic volatile impurities (OVI) and residual solvents (RS). Based on our knowledge of the manufacturing process and on controlled handling and storage of the material, we acknowledge that there is no potential for introduction of residual solvents or organic volatile impurities in the product because the only solvent in our inorganic synthesis process is water.

Typical bulk density (tapped)

44 to 49 lbs/cu.ft.
0.70 to 0.78 g/mL

Typical particle size

On 2000 µm (US standard mesh #10): 5% Max.
Through 45 µm (US standard mesh #325): 2% Max.

Packaging

20 kg, 22.7 kg and 25 kg multiwall paper bags.
45.4 kg drums.
Big bags up to 454 kg.

Storage

Store in a cool and dry place, in tight containers,
for up to 2 years.

Conforms to current Food Chemicals Codex (FCC) and National Formulary (NF) requirements.

Liability: The information submitted in this document is based on current knowledge and experience. The information contained herein is furnished without warranty of any kind. Macco Organiques Inc. does not accept any liability whatsoever in respect of the use of this information nor in respect of use, application, adaptation or processing of the product described herein. The recommended times presented in this document may vary greatly depending on storage conditions.